



V2.10

# WEEBILL LAB Camera Compatibility List

Updated on December 12th, 2018 (corresponding to the firmware version of stabilizer: V1.84, image transmission firmware version V1.15)  
 The camera models listed in the table can be balanced on the WEEBILL LAB and achieve stabilization effect when paired with compatible lenses.  
 The camera functions that WEEBILL LAB can control will be shown in the "Grip Control & APP Control" columns and will be improved as tests continue.

Brand	Camera Model	Compatible Camera Control Cable	Grip Control	APP Control	Support Image Transmission or not	Precautions for camera/ lens settings	Camera Firmware Version	Firmware Update Plan	Compatible Lens
Sony	A7	Micro usb - Micro USB	1. Take photos 2. Start/stop recording video 3. Manual follow focus (with follow focus motor) 4. Aperture adjustment 5. Shutter speed adjustment 6. ISO adjustment	1. Take photos 2. Start/stop recording video 3. Aperture adjustment 4. Shutter speed adjustment 5. ISO adjustment 6. White balance adjustment	No	1. Select MENU > USB Connection > PC Remote 2. Set the remote computer control as computer + camera device;	/	/	FE 16-35mm F2.8 GM FE 12-24mm F4 G Vario-Tessar T* FE 16-35 mm F4 ZA OSS FE 24-70 mm F2.8 GM (Only A6300 and A6500 can be balanced in 24-55mm focal length with the camera only) Vario-Tessar T* FE 24-70 mm F4 ZA OSS FE 28 mm F2 Distagon T* FE 35 mm F1.4 ZA Sonnar T* FE 35 mm F2.8 ZA Planar T* FE 50mm F1.4 ZA FE 50mm F1.8 Sonnar® T* FE 55 mm F1.8 ZA FE 85 mm F1.4 GM E 10-18 mm F4 OSS Vario-Tessar T* E 16-70 mm F4 ZA OSS E PZ 18-105 mm F4 G OSS E 18-200 mm F3.5-6.3 OSS LE (Can be balanced in 18-55mm focal length without removing eyepiece cover) Sonnar® T* E 24 mm F1.8 ZA (SIGMA) 30mm F1.4
	A7S				Yes		/	/	
	A7S2				Yes		/	/	
	A7R				No		/	/	
	A7R2				Yes		/	/	
	A7R3				Yes		/	/	
	A7M2				Yes		/	/	
	A7M3				Yes		/	/	
	A6000				No		V3.20	/	
	A6300				Yes		V1.10	/	
	A6500				Yes		V1.05	/	

Brand	Camera Model	Compatible Camera Control Cable	Grip Control	APP Control	Support Image Transmission or not	Precautions for camera/ lens settings	Camera Firmware Version	Firmware Update Plan	Compatible Lens
Panasonic	GH5s	Micro USB - TYPE C	1. Take photos 2. Start/stop recording video 3. Manual follow focus (with follow focus motor) 4. Aperture adjustment 5. Shutter speed adjustment 6. ISO adjustment Start/stop the video	1. Take photos 2. Start/stop recording video 3. Aperture adjustment 4. Shutter speed adjustment 5. ISO adjustment 6. White balance adjustment	Yes	Set the camera USB mode to PC (Tether)	V1.1		LEICA DG Vario-Elmarit 8-18mm f/2.8-4.0 ASPH Lumix G X Vario 12-35mm f/2.8 II ASPH POWER OIS LEICA DG SUMMILUX 15mm f/1.7 ASPH Lumix G 25mm f/1.7 (H-H025GK) LUMIX G MACRO 30mm f/2.8 ASPH MEGA OIS
	GH5				Yes		V2.2		
Nikon	Z6	Micro USB-TYPE C	1. Take photos 2. Start/stop recording video 3. Manual follow focus (with follow focus motor) 4. Aperture adjustment 5. Shutter speed adjustment 6. ISO adjustment	1. Take photos 2. Start/stop recording video 3. Aperture adjustment 4. Shutter speed adjustment 5. ISO adjustment 6. White balance adjustment"	Yes	Directly connect the camera with the stabilizer"	V1.00	/	AF-S NIKKOR 24mm f/1.8G ED AF-S NIKKOR 50MM F/1.8G AF-S NIKKOR 50MM F/1.4G AF-S NIKKOR 85mm f/1.8G Nikkor Z 35mm f/1.8
	Z7				Yes		V1.02	/	

Note: 1.This table will be updated in line with the firmware and is subject to change without a prior notice.  
 2. Balance adjustment is shown in the attached table.  
 3.Camera models that are not listed in the table will be tested in the future according to market feedback.  
 4. SONY A7/ A7S/A7S2/A7R/A7R2/A7M2/A6000/A6300 cannot support to look back photos or video. Photos shot with panorama and timelapse cannot be stored in the camera.  
 5. For SONYA7/ A7S/A7S2/A7R/A7R2/A7M2/A6000/A6300, don't turn on the stabilizer under the video mode when applying the image transmission feature. If you need to use video mode, please turn on the stabilizer under other modes and switch back to the video mode.  
 6. When the Sony and Nikon cameras connect to the WEEBILL LAB under the video mode and needs to connect to the recorder or HDMI external device, the external device is not available. When WEEBILL LAB connects to the camera with the Steadyshot feature, part of the cameras will shut down automatically.  
 7. Image transmission is not available on Sony A7/A7R/A6000.



# WEEBILL LAB Camera Compatibility List

## Attached Table:

1. "Can be balanced at any focal length" means the balance adjustment can be achieved for the both ends of the zoom lens.
2. The follow focus is installed with the lens pointing direction as the front, which can be mounted on the left or right side of the lens to achieve focus or zoom control (the installation mode is not fixed and you can try it by yourself);
3. The camera models and lenses that are not listed in the table can be tested by users. The cameras and lenses that can achieve balance adjustment and are within the payload can be mounted on the WEEBILL LAB.

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark
Sony	A7M3	E 10-18mm F4 OSS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		FE 12-24mm F4 G	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
		FE 16-35mm F2.8 GM	Camera only	√	√	Can be balanced at any focal length and need to remove eyepiece cover		
			With follow focus motor(focus)	×				
			With follow focus motor(zoom)	×				
		Vario-Tessar T* E 16-70mm F4 ZA OSS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover	Can be balanced at any focal length	
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		E PZ 18-105mm F4 G OSS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover		
		E 18-200mm F3.5-6.3 OSS LE	Camera only	√	×	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length and need to remove eyepiece cover	
			With follow focus motor(focus)	√	×	Can be balanced in 18-50mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side
			With follow focus motor(zoom)	√	×	Can be balanced in 18-35mm focal length if the eyepiece cover is not removed	Can be balanced in 18-110mm focal length if the eyepiece cover is removed	The follow focus motor can be mounted on both sides
		FE 28mm F2	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)					
FE 24-70 mm F2.8 GM	Camera only	×						
FE 24-70mm F4 ZA OSS	Camera only	√	×	No need to remove eyepiece cover	Can be balanced at any focal length			
	With follow focus motor(focus)	√	×	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides			
	With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides			



## WEEBILL LAB Camera Compatibility List

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark
Sony	A7M3	Sonnar T* FE 35mm F2.8 ZA	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)					
		Sigma 30mm f/1.4 DC DN	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)					
		Distagon T* FE 35 mm F1.4 ZA	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)					
		FE 50mm F1.8	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)					
		Sonnar T* FE 55mm F1.8 ZA	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)					
		FE 85mm F1.4 GM	Camera only	√	√	Need to remove eyepiece cover		The vertical direction of the tilt axis is slightly unbalanced, and the holder of the follow focus can be clamped to the rear of the camera backing base.
			With follow focus motor(focus)	√	√	Need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
			With follow focus motor(zoom)					
	A7R3	E 10-18mm F4 OSS	Camera only	√	×			
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		FE 12-24mm F4 G	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
FE 16-35mm F2.8 GM		Camera only	√	√	Can be balanced at any focal length and need to remove eyepiece cover			
		With follow focus motor(focus)	×					
		With follow focus motor(zoom)	×					
Vario-Tessar T* E 16-70mm F4 ZA OSS		Camera only	√	×		Can be balanced at any focal length		
		With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
		With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides		

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark	
Sony	A7R3	E PZ 18-105mm F4 G OSS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover			
		E 18-200mm F3.5-6.3 OSS LE	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover	Can be balanced at any focal length and need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
			With follow focus motor(zoom)	√	×	Can be balanced in 18-50mm focal length if the eyepiece cover is not removed	Can be balanced in 18-110mm focal length if the eyepiece cover is removed	The follow focus motor can be mounted on both sides	
		FE 24-70mm F4 ZA OSS	Camera only	√	×	Can be balanced in 18-35mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length		
			With follow focus motor(focus)	√	×	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
		FE 24-70 mm F2.8 GM	Camera only	×					
		FE 28mm F2	Camera only	√	×				
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)			No need to remove eyepiece cover			
		Sigma 30mm f/1.4 DC DN	Camera only	√	×				
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)			No need to remove eyepiece cover			
		Distagon T* FE 35 mm F1.4 ZA	Camera only	√	×				
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)			Need to remove eyepiece cover			
		Sonnar T* FE 35mm F2.8 ZA	Camera only	√	×	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)						
		FE 50mm F1.8	Camera only	√	×	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)						
		Sonnar T* FE 55mm F1.8 ZA	Camera only	√	×	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)						
		FE 85mm F1.4 GM	Camera only	√	√	Need to remove eyepiece cover	The vertical direction of the tilt axis is slightly unbalanced, and the holder of the follow focus can be clamped to the rear of the camera backing base.		
			With follow focus motor(focus)	√	√	Need to remove eyepiece cover	The follow focus motor should be mounted on the left side		
With follow focus motor(zoom)									

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark
Sony	A7S2	E 10-18mm F4 OSS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		FE 12-24mm F4 G	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
		FE 16-35mm F2.8 GM	Camera only	√	√	Can be balanced at any focal length and need to remove eyepiece cover		
			With follow focus motor(focus)	×				
			With follow focus motor(zoom)	×				
		Vario-Tessar T* E 16-70mm F4 ZA OSS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		E PZ 18-105mm F4 G OSS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	electronic zoom and no need to mount a follow focus motor	Can be balanced at any focal length and no need to remove eyepiece cover		
		E 18-200mm F3.5-6.3 OSS LE	Camera only	√	×	Can be balanced in 18-55mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length and need to remove eyepiece cover	
			With follow focus motor(focus)	√	×	Can be balanced in 18-50mm focal length if the eyepiece cover is not removed	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side
			With follow focus motor(zoom)	√	×	Can be balanced in 18-35mm focal length if the eyepiece cover is not removed	Can be balanced in 18-110mm focal length if the eyepiece cover is removed	The follow focus motor can be mounted on both sides
		FE 24-70mm F4 ZA OSS	Camera only	√	×	No need to remove eyepiece cover	Can be balanced at any focal length	
			With follow focus motor(focus)	√	×	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		FE 24-70 mm F2.8 GM	Camera only	×				
		FE 28mm F2	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
With follow focus motor(zoom)								
Sigma 30mm f/1.4 DC DN	Camera only	√	×	No need to remove eyepiece cover				
	With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides			
	With follow focus motor(zoom)							



## WEEBILL LAB Camera Compatibility List

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark
Sony	A7S2	Distagon T* FE 35 mm F1.4 ZA	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)					
		Sonnar T* FE 35mm F2.8 ZA	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)					
		FE 50mm F1.8	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)					
		Sonnar T* FE 55mm F1.8 ZA	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)					
	FE 85mm F1.4 GM	Camera only	√	√	Need to remove eyepiece cover		The vertical direction of the tilt axis is slightly unbalanced, and the holder of the follow focus can be clamped to the rear of the camera backing base.	
		With follow focus motor(focus)	√	√	Need to remove eyepiece cover	The follow focus motor should be mounted on the left side		
		With follow focus motor(zoom)						
	A6500	E 10-18mm F4 OSS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		FE 12-24mm F4 G	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor should be mounted on the left side	
		FE 16-35mm F2.8 GM	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
Vario-Tessar T* E 16-70mm F4 ZA OSS		Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover	Can be balanced at any focal length		
		With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
		With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides		

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark	
Sony	A6500	E PZ 18–105mm F4 G OSS	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			electronic zoom ( no need to mount a follow focus motor)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover			
		E 18–200mm F3.5–6.3 OSS LE	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover			
			With follow focus motor(focus)	√	×	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor should be mounted on the left side		
			With follow focus motor(zoom)	√	×	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
		FE 24–70mm F4 ZA OSS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover			
			With follow focus motor(focus)	√	×	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
		FE 24-70 mm F2.8 GM	Camera only	√	√	Can be balanced at 24-50mm focal length			
			With follow focus motor(focus)	×					
			With follow focus motor(zoom)	×					
		FE 28mm F2	Camera only	√	×	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)						
		Sigma 30mm f/1.4 DC DN	Camera only	√	×	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)						
		Distagon T* FE 35 mm F1.4 ZA	Camera only	√	√	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)						
		Sonnar T* FE 35mm F2.8 ZA	Camera only	√	×	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor should be mounted on the left side		
			With follow focus motor(zoom)						
		FE 50mm F1.8	Camera only	√	√	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)						
		Sonnar T* FE 55mm F1.8 ZA	Camera only	√	×	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
			With follow focus motor(zoom)						
FE 85mm F1.4 GM	Camera only	√	√	No need to remove eyepiece cover					
	With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides				
	With follow focus motor(zoom)								





# WEEBILL LAB Camera Compatibility List

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark
Panasonic	GH5s GH5	LEICA DG Vario-Elmarit 8-18mm f/2.8-4.0 ASPH	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Lumix G X Vario 12-35mm f/2.8 II ASPH POWER OIS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		LEICA DG SUMMILUX 15mm f/1.7 ASPH	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	The follow focus motor should be mounted on the right side		
			With follow focus motor(zoom)					
	Lumix G 25mm f/1.7 (H-H025GK)	Camera only	√	×	No need to remove eyepiece cover			
		With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
		With follow focus motor(zoom)						
	LUMIX G MACRO 30mm f/2.8 ASPH MEGA OIS	Camera only	√	×	No need to remove eyepiece cover			
		With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
		With follow focus motor(zoom)						



# WEEBILL LAB Camera Compatibility List

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark
Fujifilm	XT3	XF 18-55mm f/2.8-4 R OIS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		XF 16-55mm f/2.8 R LM WR	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		XF 23mm f/1.4 R	Camera only	√	√	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		XF 18-135mm f/3.5-5.6 R LM OIS WR	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	Can be balanced at any focal length	
			With follow focus motor(focus)	√	√	Can be balanced at 18-70mm focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at 18-105mm focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		XF 10-24mm f/4.0 R OIS	Camera only	√	×	No need to remove eyepiece cover		
	With follow focus motor(focus)		√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	With follow focus motor(zoom)		√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	XF 35mm f/2 R WR	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover			
		With follow focus motor(focus)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	XT2	XF 18-55mm f/2.8-4 R OIS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		XF 16-55mm f/2.8 R LM WR	Camera only	√	√	Can be balanced at any focal length and no need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		Super EBC XF 23mm f/1.4 R	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
XF 18-135mm f/3.5-5.6 R LM OIS WR		Camera only	√	√	Can be balanced at any focal length and need to remove eyepiece cover	Can be balanced at any focal length		
		With follow focus motor(focus)	√	√	Need to remove eyepiece cover	Can be balanced at 18-70mm focal length and mounted on the right side		
		With follow focus motor(zoom)	√	√	Can be balanced at any focal length and need to remove eyepiece cover	Can be balanced at any focal length		
XF 10-24mm f/4.0 R OIS		Camera only	√	×	No need to remove eyepiece cover			
	With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides			
	With follow focus motor(zoom)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides			
XF 35mm f/2 R WR	Camera only	√	×	No need to remove eyepiece cover				
	With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on the right side			

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark	
Fujifilm	XH1	XF 18-55mm f/2.8-4 R OIS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover			
			With follow focus motor(focus)	√	×	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on the right side	The follow focus motor can be mounted on the left side and the roll axis is slightly unbalanced	
			With follow focus motor(zoom)	√	×	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on the right side	The follow focus motor can be mounted on the left side and the roll axis is slightly unbalanced	
		XF 16-55mm f/2.8 R LM WR	Camera only	√	×	Can be balanced at any focal length and need to remove eyepiece cover			
			With follow focus motor(focus)	×	×				
			With follow focus motor(zoom)	×	×				
		Super EBC XF 23mm f/1.4 R	Camera only	√	×	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on the right side		
		XF 18-135mm f/3.5-5.6 R LM OIS WR	Camera only	√	×	Can be balanced at any focal length and need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	Can be balanced at 18-23mm focal length and need to remove eyepiece cover	The follow focus motor can be mounted on the right side		
			With follow focus motor(zoom)	√	√	Can be balanced at 18-23mm focal length and need to remove eyepiece cover	The follow focus motor can be mounted on the right side		
		XF 10-24mm f/4.0 R OIS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover		The follow focus motor can be mounted on both sides	
			With follow focus motor(zoom)	√	√	No need to remove eyepiece cover		The follow focus motor can be mounted on both sides	
		XF 35mm f/2 R WR	Camera only	√	×	No need to remove eyepiece cover			
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on the right side		
		XT20	XF 18-55mm f/2.8-4 R OIS	Camera only	√	×	Can be balanced at any focal length and no need to remove eyepiece cover		
				With follow focus motor(focus)	√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on the right side	
	With follow focus motor(zoom)			√	√	Can be balanced at any focal length and no need to remove eyepiece cover	The follow focus motor can be mounted on the right side		
	XF 16-55mm f/2.8 R LM WR		Camera only	×		The eyepiece cover cannot be removed			
			With follow focus motor(focus)	√	√	Can be balanced at 16-35mm focal length and the eyepiece cover cannot be removed	The follow focus motor can be mounted on the right side		
	With follow focus motor(zoom)		√	√	Can be balanced at 16mm focal length and the eyepiece cover cannot be removed	The follow focus motor can be mounted on the right side			
			Super EBC XF 23mm f/1.4 R	Camera only	√	√	No need to remove eyepiece cover		
	With follow focus motor(focus)		√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on the right side			
XF 18-135mm f/3.5-5.6 R LM OIS WR	Camera only		√	√	Can be balanced at any focal length and no need to remove eyepiece cover	Slightly rub when balanced at 135 mm focal length			
	With follow focus motor(focus)		√	√	Cannot be balanced at any focal length and the eyepiece cover cannot be removed	The follow focus motor can be mounted on the right side			
	With follow focus motor(zoom)		√	√	Cannot be balanced at any focal length and the eyepiece cover cannot be removed	The follow focus motor can be mounted on the right side			
XF 10-24mm f/4.0 R OIS	Camera only		√	√	Can be balanced at any focal length and the eyepiece cover cannot be removed				
	With follow focus motor(focus)		√	√	Can be balanced at any focal length and the eyepiece cover cannot be removed	The follow focus motor can be mounted on the right side			
	With follow focus motor(zoom)		√	√	Can be balanced at any focal length and the eyepiece cover cannot be removed	The follow focus motor can be mounted on the right side			
XF 35mm f/2 R WR	Camera only		√		Can be balanced at any focal length and no need to remove eyepiece cover				
	With follow focus motor(focus)		√		No need to remove eyepiece cover	The follow focus motor can be mounted on both sides			



## WEEBILL LAB Camera Compatibility List

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark
Canon	EOS R	EF 40mm f/2.8 USM	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		EF 50mm f/1.8 STM	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		EF 50mm f/1.4 USM	Camera only	√		No need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
		RF 35mm f/1.8 Macro IS STM	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	No need to remove eyepiece cover		
		EF 85mm f/1.4 IS L USM	Camera only	×	×			
			With follow focus motor(focus)	×				
		EF 85mm f/1.8	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	×	No need to remove eyepiece cover	The follow focus motor can be mounted on the right side	



## WEEBILL LAB Camera Compatibility List

Camera Brand	Camera Model	Lens Type	Installation	Balance Adjustment	Need a Camera Backing Base or not	Balance Adjustment with Camera Only	Follow Focus Motor Installation	Remark
Nikon	Z6	AF-S NIKKOR 24mm f/1.8G ED	Camera only	√	×	Need to remove eyepiece cover		
			With follow focus motor(focus)	×	×			
		AF-S NIKKOR 50MM F/1.8G	Camera only	√	×			
			With follow focus motor(focus)	√	×			
		AF-S NIKKOR 50MM F/1.4G	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	AF-S NIKKOR 85mm f/1.8G	Camera only	√	×	Need to remove eyepiece cover			
		With follow focus motor(focus)	×					
	Nikkor Z 35mm f/1.8	Camera only	√	×	No need to remove eyepiece cover			
		With follow focus motor(focus)	√	√	Need to remove eyepiece cover	The follow focus motor can be mounted on both sides		
	Z7	AF-S NIKKOR 24mm f/1.8G ED	Camera only	√	×	Need to remove eyepiece cover		
			With follow focus motor(focus)	×	×			
		AF-S NIKKOR 50MM F/1.8G	Camera only	√	×			
			With follow focus motor(focus)	√	×			
		AF-S NIKKOR 50MM F/1.4G	Camera only	√	×	No need to remove eyepiece cover		
			With follow focus motor(focus)	√	√	Need to remove eyepiece cover	The follow focus motor can be mounted on both sides	
	AF-S NIKKOR 85mm f/1.8G	Camera only	√	×	Need to remove eyepiece cover			
		With follow focus motor(focus)	×					
Nikkor Z 35mm f/1.8	Camera only	√	×	No need to remove eyepiece cover				
	With follow focus motor(focus)	√	√	Need to remove eyepiece cover	The follow focus motor can be mounted on both sides			